

## Rechargeable Li-ion Battery

**2S1P  
(60 watt)**



**2S1P Battery Pack (60 watt)**

Features:

- Rating:DC 7.2V, 2750 mAh
- Work with PW405 / PW407
- 20 x 65 x 40 mm

**2S1P  
(30 watt)**



**2S1P Battery Pack (30 watt)**

Features:

- Rating:DC 7.4V, 3200 mAh
- Work with PW405, PW406
- 10 x 85 x 65 mm

**2S3P  
(60 watt)**



**2S3P Battery Pack(60 watt)**

Features:

- Rating: DC 7.2V, 8500 mAh
- Work with PW405 / PW407
- 20 x 120 x 65 mm

**2S3P  
(30 watt)**



**2S3P Battery Pack (30 watt)**

Features:

- Rating:DC 7.4V, 9600 mAh
- Work with PW405, PW406
- 10 x 125 x 65 mm

## Power Board

**PW501**



**Isolated Wide Range Power board**

Features:

- Input: DC IN 18V~36V / 18V~75V / 9V~36V
- Output: 4 x +12V DC output (Optional to 24V DC output)
- Power: 120W
- 73 x 45 mm

**PW504**



**Isolated power with CPC**

Features:

- Delta 1 / 8 brick module
- CPC function onboard
- eIO output (option)
- 93 x 45mm

**PW502**



**Isolated Wide range Power board**

Features:

- Input Voltage: 18V~75V, 9V~36V or 16.6V~154V
- Output: 4 x +12V DC output (Optional to 24V)
- Operating base plate temperature -40°C to +100°C
- Isolation voltage: 3000V
- Power: 200W
- 102 x 73 mm

**PW503**



**Isolated Wide range Power board**

Features:

- Input Voltage: 43V~160V
- Output: 5 x +12V DC output
- Operating base plate temperature -40°C to +100°C
- Isolation voltage: 3000V
- Power: 200W
- 102 x 73 mm