Embedded Function Cards



USB to 1 x RS232 / RS485

Features:

- M303A-232: USB to RS232
- M303A-485: USB to RS485
- 30.81 x 15 mm



eDP to LVDS module

Features:

- Module Input voltage: +5V to +12V
- eDP to LVDS 24bits / Dual channel output.
- 35 X 35 mm



RS232 to RS422 / RS485

Features:

- CC004-2T4: RS232 to RS422 / 485
- CC004-2T5: RS232 to RS485
- 31 x 25 mm



eDP to DVI converter board

Features:

- eDP to DVI
- 25 x 40.5 mm



RS232 to ISO RS232

Features:

- RS232 to Isolator RS232 TX/RX/GND
- 31 x 25 mm



eDP to VGA board

Features:

- eDP to VGA
- 31 x 30 mm



RS232 to ISO RS422 / 485

Features

- RS232 to Isolator RS422 / 485
- 31 x 25 mm



SATA to CFast slot

Features:

- Support +3.3V
- Support CFast Card Type I / II
- 53 x 67 mm



RS232 to ISO RS485

Features:

- RS232 to Isolator RS485
- 36.8 x 25 mm



SATA to 2 x CFAST RAID 0 / 1

Features:

- Support +3.3V
- Support CFast Card Type I / II
- 93 x 56 mm



USB to SD Card Reader

Features:

- NO support OS boot
- USB to SD interface
- 55 x 35 mm