


2I380D


Pico-ITX SBC supports Intel® Bay Trail Atom / Celeron CPU
3 x Intel Gb Ethernet, VGA, 4 x USB,
2 x COM, 1 x Mini PCIe, 1 x M.2, SMBus



Features:

- Intel® Bay Trail-H Atom™ E3825 1.33GHz (Dual Core)
Intel® Bay Trail-H Atom™ E3845 1.91 GHz (Quad Core)
Intel® Bay Trail-D Celeron® J1900 2.0GHz (Quad Core)
- On Board DDR3L 1066 / 1333 MHz 2GB / 4GB
- Independent display: VGA
- 3 x Intel GbE LAN, 1 x USB 3.0, 3 x USB 2.0
- 2 x COM, 1 x Mini PCIe, 1 x M.2, SMBus

Dimensions: (Unit:mm)



Specifications :

- CPU**
Intel® Bay Trail-H Atom™ E3825 1.33GHz (Dual Core)
Intel® Bay Trail-H Atom™ E3845 1.91 GHz (Quad Core)
Intel® Bay Trail-D Celeron® J1900 2.0GHz (Quad Core)
- MB Chipset**
Intel® Bay Trail SoC
- Graphics**
Intel Gen7 graphic engine
DirectX11, OpenGL3.2, OpenCL1.1 ; Full HW acceleration,
decode: H.264, MPEG 2 / 4, VC-1, WMV9. Encode: H.264, MPEG2
- System Memory**
On Board DDR3L 1066 / 1333 MHz 2GB / 4GB
- Storage**
1 x M.2 B Key, Type 2242 (SATA)
1 x mini card socket for mSATA
- BIOS**
Insyde UEFI BIOS
- Display**
1 x VGA
- LAN**
3 x Intel GbE (external)
- Expansion Interface**
1 x Full size Mini PCIe (mSATA / USB)

Expansion Module

Converter Card	CN066: Mini PCIe to M.2 E key 2230, WiFi 6 + BT
Mini Card	GPS, 3G / 4G, Wi-Fi, 2 / 4 x LAN, 4 x COM, CANBus, SDI / AHD Video
By Cable	Bluetooth, Digital I/O, 2 / 4 PoE, 4 x USB mini card

- USB**
1 x USB 3.0 (external), 3 x USB 2.0 (external)
- USB Expansion**
USB to COM, Mini Card, M.2, Audio board
- Serial IO**
2 x RS232 / 422 / 485 (internal)
- SMBus**
1 x SMBus
- WDT**
Hardware Watch Dog Timer, 0~255 sec programmable
- Power Input**
Wide Range +12~24V
- Dimension**
90.8 x 76.25 mm
- Operation Temperature**
-20°C~70°C (100 % CPU Usage)
- Operation Humidity**
5~95%, non-condensing
- Chassis (OEM I/O Expansion by request)**
Box PC: NET-I
- OS Support**

Windows® 10 IOT (64bit), Windows® 8.1 (64bit), Windows® Embedded 8 Standard (64bit),
Windows® 7 (32 / 64bit), Windows® Embedded Standard 7 Runtime,
Ubuntu 14.10 above, Fedora 25 above, Debian 8 above, CentOS 7.3 above,
Mint 18.1 above