



TASK-3I610CW

Fanless Embedded Computer with
6th / 7th Gen Intel® Skylake-U /
Kaby Lake-U i7 / i5 / i3 processor

■ Features:

- 6th / 7th Gen Intel® Skylake-U / Kaby Lake-U i7 / i5 / i3 processor
- 1 x DDR4 SODIMM socket, Max. 32GB
- Independent display: VGA & DVI
- 2 x Intel GbE LAN, 4 x USB 3.0, 6 x COM
- 2 x Mini PCIe, 1 x SIM

■ Specifications :

Motherboard	3I610CW	
CPU	6th / 7th Gen Intel® Skylake-U / Kaby Lake-U i7 / i5 / i3 CPU	
Chipset	Intel® Skylake-U / Kaby Lake-U SoC	
Memory	1 x DDR4 SODIMM socket, Max. 32GB	
Storage	mSATA, HDD / SSD*	
Expansion slots	1 x Full-size Mini PCIe (mSATA / USB) 1 x Full-size Mini PCIe (PCIe / USB 2.0) 1 x SIM	
I/O ports	Network	2 x Intel GbE
	USB	4 x USB 3.0
	Serial ports	6 x RS232 / 422 / 485
	Display	VGA & DVI
	GPIO	DI / DO (Option)
Optional Modules & Accessory	GPS, Bluetooth, PoE, WiFi, 4G LTE, Isolated COM, battery UPS, DI/DO, Video Input *SATA Kit, VESA Mounting Kit	
OS Support	7th Generation Intel® Core™ Processor family: Kaby Lake Windows® 10 IOT (64bit), Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above 6th Generation Intel® Core™ Processor family: Skylake Windows® 10 IOT (64bit) Windows® 8.1 (64bit) Windows® Embedded 8 Standard (64bit) Windows® 7 (64bit) Windows® Embedded Sta 7 (64bit) Ubuntu 16.04.3 above, Fedora 26 above, CentOS 7.4 above	

■ Mechanical

Dimensions 210W x 125D x 77H mm

Weight 1.9 kg

Mounting VESA Mount*

■ Power

DC input +9~36V

AC input External adapter 100 / 240V ; AC-DC 60W

■ Environment

Operating Temp. -20°C to +60°C (Celeron 3955U)

(100 % CPU usage) -20°C to +50°C (Core i5 6300U)

-20°C to +50°C (Core i7 6600U)

-20°C to +50°C (Core i3 6100U)

*W / Industrial SSD


Storage Temp. -20°C to +70°C

Relative Humidity 95% @ 40°C, non-condensing

■ Certification

CE / FCC class A

■ Dimension



Specification are subject to change without prior notice. ODM / OEM is available.