


21385S(W)


Pico-ITX SBC supports Intel® Bay Trail Atom / Celeron CPU
VGA, HDMI, mini HDMI, 2 x Intel Gb Ethernet
3 x USB, 2 x Mini PCIe, SMBus



Features:

- Intel® Bay Trail-H Atom™ E3825 1.33GHz (Dual Core)
Intel® Bay Trail-H Atom™ E3845 1.91 GHz (Quad Core)
Intel® Bay Trail-D Celeron® J1900 2.0GHz (Quad Core)
- On Board DDR3L 1066 / 1333 MHz 2GB / 4GB
- Multiple Independent display: VGA , HDMI, mini HDMI
- 2 x Intel GbE LAN, 1 x USB 3.0, 1 x USB 2.0, 1 x Micro USB 2.0
- 2 x Mini PCIe, SMBus

Dimensions: (Unit:mm)



Specifications :

- CPU**
Intel® Bay Trail-H Atom™ E3825 1.33GHz (Dual Core)
Intel® Bay Trail-H Atom™ E3845 1.91 GHz (Quad Core)
Intel® Bay Trail-D Celeron® J1900 2.0GHz (Quad Core)
- MB Chipset**
Intel® Bay Trail SoC
- Graphics**
Intel Gen7 graphic engine
DirectX11, OpenGL3.2, OpenCL1.1 ; Full HW acceleration,
decode: H.264, MPEG 2 / 4, VC-1, WMV9. Encode: H.264, MPEG2
- System Memory**
On Board DDR3L 1066 / 1333 MHz 2GB / 4GB
- Storage**
2 x mini card socket for mSATA
- BIOS**
Insyde UEFI BIOS
- Display**
1 x VGA, 1 x HDMI, 1 x mini HDMI
- LAN**
2 x Intel GbE (external)
- Audio**
High Definition Audio, Line-out / Mic-in
- Expansion Interface**
1 x Full size Mini PCIe (PCIe / mSATA / USB)
1 x Half size Mini PCIe (mSATA / USB) share with Micro USB

Expansion Module

Converter Card	CN066: Mini PCIe to M.2 E key 2230, WiFi 6 + BT
Mini Card	GPS, 3G / 4G, Wi-Fi, 2 / 4 x LAN, 4 x COM, CANBus, SDI / AHD Video
By Cable	Bluetooth, Digital I/O, 2 / 4 PoE, 4 x USB mini card

- USB**
1 x USB 3.0 (external), 1 x USB 2.0 (external)
1 x Micro USB 2.0 (external)

USB Expansion

USB to	COM, Mini Card, M.2, Audio board
---------------	----------------------------------

- Serial IO**
Optional
- SMBus**
1 x SMBus
- WDT**
Hardware Watch Dog Timer, 0~255 sec programmable
- Power Input**
DC IN+12V ; optional +9~36V
- Dimension**
Pico-ITX 2.5" (102 x 73 mm)
- Operation Temperature**
-20°C~70°C (100 % CPU Usage)
- Operation Humidity**
5~95%, non-condensing
- Chassis (OEM I/O Expansion by request)**
Box PC: BLADE, TWIN
- OS Support**
Windows® 10 IOT (64bit), Windows® 8.1 (64bit), Windows® Embedded 8 Standard (64bit),
Windows® 7 (32 / 64bit), Windows® Embedded Standard 7 Runtime,
Ubuntu 14.10 above, Fedora 25 above, Debian 8 above, CentOS 7.3 above,
Mint 18.1 above

Specification are subject to change without prior notice. ODM / OEM is available.