

2I385PW


Pico Express Computer on Module supports
 Intel® Bay Trail Atom / Celeron CPU
 VGA, HDMI, LVDS, Touch, 2 x Intel Gb Ethernet,
 4DI / 4DO, 6 x USB, 4 x COM, 2 x Mini PCIe, 1 x PCIe



Features:

- Intel® Bay Trail-H Atom™ E3825 1.33GHz (Dual Core)
 Intel® Bay Trail-H Atom™ E3845 1.91 GHz (Quad Core)
 Intel® Bay Trail-D Celeron® J1900 2.0GHz (Quad Core)
- On Board DDR3L 1066 / 1333 MHz 2GB / 4GB
- Multiple Independent display: VGA, HDMI & LVDS
- 2 x Intel GbE LAN, 1 x USB 3.0, 5 x USB 2.0
- 4 x COM, 4DI / 4DO, 2 x Mini PCIe, 1 x PCIe

Dimensions: (Unit:mm)



Specifications :

- CPU**
 Intel® Bay Trail-H Atom™ E3825 1.33GHz (Dual Core)
 Intel® Bay Trail-H Atom™ E3845 1.91 GHz (Quad Core)
 Intel® Bay Trail-D Celeron® J1900 2.0GHz (Quad Core)
- MB Chipset**
 Intel® Bay Trail SoC
- Graphics**
 Intel Gen7 graphic engine
 DirectX11, OpenGL3.2, OpenCL1.1 ; Full HW acceleration,
 decode: H.264, MPEG 2 / 4, VC-1, WMV9. Encode: H.264, MPEG2
- System Memory**
 On Board DDR3L 1066 / 1333 MHz 2GB / 4GB
- Storage**
 1 x SATA ports 2.0 Data transfer rates up to 3.0 Gb/s (300 MB/s), Share with mSATA 2
 2 x mini card socket for mSATA
- BIOS**
 Insyde UEFI BIOS
- Display**
 1 x VGA, 1 x HDMI, Dual Channel, 48 bits LVDS
- Touch**
 COM touch screen controller
- LAN**
 2 x Intel GbE (internal)
- Audio**
 High Definition Audio Specification, Support Line-out / Mic-in / Line-in
 Two channel Class D Audio Amplifier
- Expansion Interface**
 1 x Full size Mini PCIe (PCIe / mSATA / USB)
 1 x Full size Mini PCIe (mSATA)
 1 x PCIe 1x
 Pico Express 160-pin connector

Expansion Module

IO expanded via 160-pin connector

Carrier Board :

DK001: DVI, VGA, 5 x USB, 2 x LAN, 4 x COM, 4 x Mini PCIe, 4 x SIM

DK002: HDMI, VGA, 5 x USB, 2 x LAN, 4 x COM, 2 x Mini PCIe, 2 x SIM

DK006: VGA, 5 x USB, 2 x LAN, 4 x COM, 4 x BNC Board

DK007: VGA, 5 x USB, 4 x COM, 2 x PoE, 2 x Mini PCIe, 2 x SIM

DM002: M12 Board (mini HDMI, VGA, 2 x USB, 4 x COM, 2 x GbE, 1 x Mini PCIe, 1 x SIM)

- USB**
 1 x USB 3.0 (internal), 5 x USB 2.0 (internal)
- Serial IO**
 4 x RS232 / 422 / 485 (internal)
- GPIO**
 Hardware digital Input & Output, 4 x DI / 4 x DO
- WDT**
 Hardware Watch Dog Timer, 0~255 sec programmable
- PS2 KB / MS**
 PS2 KB / MS
- Power Input**
 Wide Range +9~36V
- Dimension**
 Pico-ITX 2.5" (102 x 73 mm)
- Operation Temperature**
 -20°C~70°C (100 % CPU Usage)
- Operation Humidity**
 5~95%, non-condensing
- Chassis (OEM I/O Expansion by request)**
 Box PC: TWIN, TINO, ARK-I
- OS Support**
 Windows® 10 IOT (64bit), Windows® 8.1 (64bit), Windows® Embedded 8 Standard (64bit),
 Windows® 7 (32 / 64bit), Windows® Embedded Standard 7 Runtime,
 Ubuntu 14.10 above, Fedora 25 above, Debian 8 above, CentOS 7.3 above,
 Mint 18.1 above

Specification are subject to change without prior notice. ODM / OEM is available.