

NF226B

M.2 B+M key 3042 PCIe to 2 Port 2.5GbE LAN board

Introduction:

Intel I226-IT LAN Chip


Top



Features:

- Uses Intel I226IT LAN chipset for PCIe Gen2 x 1 V3.1 interface.
- I226IT Extended temperature: -40°C to +85°C
- Flow control support: send / receive PAUSE frames and receive FIFO thresholds
- IEEE 802.3az Energy Efficient Ethernet (EEE)
- IEEE 802.1q VLAN support
- Audio-video bridging (AVB) support
- IEEE 1588 / 802.1AS precision time synchronization
- IEEE 802.1Qav traffic shaper (with software extensions)
- Jumbo frames size 9.5KB
- Interrupt moderation, VLAN support, IP checksum offload
- PCIe OBFF (Optimized Buffer Flush / Fill) for improved system power management Four transmit and four receive 4 queues of per port.
- RSS and MSI-X to lower CPU utilization in multi-core systems
- Advanced cable diagnostics, auto MDI-X
- Vital Product Data (VPD). VPD Size 1024B
- ECC-error correcting memory in packet buffers

Mechanical Drawing:




Specification:


Type	M.2 B+M key 3042 PCIe to 2 port 2.5GbE LAN
Input I/F	PCIe Gen2 x 1
Output I/F	2 x 8 pin wafer connector
Operating Temperature	-40°C ~ +85°C
Dimensions	30 x 42 mm

Cable information:

6G6002-5040-0100



6G6002-8018-0100 L=20cm, 4p/1.25 to 4p/1.25



Specification are subject to change without prior notice. ODM / OEM is available.

■ I/O Option:


- **CL001-001**
6G9103-0001001-0




- **CL002-RJ45-001**
6G9103-0003001-0



■ Mechanical Drawing:



■ Mechanical Drawing:



■ PoE Option:

- **PW352-M12-001**
6G9102-0027001-0



- **PW352-RJ45-002**
6G9102-0017002-0



- **PW301-PDRH-001**
6G9102-0010001-0



■ Mechanical Drawing:

