

ROCK 2NOR01

Fanless AI Box:

NVIDIA® Jetson Orin™ Nano (Super) / NX SoM + 2NOR01



- CPU Board:
NVIDIA Jetson Nano (Super): 4 / 8GB LPDDR5, 20 / 40 TOPs
NVIDIA Jetson NX: 8 / 16GB LPDDR5, 70 / 100 TOPs
- AI Accelerator: NVIDIA® Jetson Orin™ Nano (Super) / Orin™ NX
- 1 x HDMI®
- 4 x USB 3.1
- Mic-in / Line-out
- 2 x RS232 (Option RS422)
- 1 x CANBus (Option)
- 2 x M.2 B key
- 4DI / 4DO (Option)
- Internal wafer: SPI, I²S, I²C, USB 2.0
- 2 x 2.5GbE, 1 x GbE
- 1 x Type C USB 3.1 / 2.0 (OTG)
- 1 x M.2 M key
- 1 x Nano SIM

Specifications :

Motherboard	NVIDIA Jetson Orin SOM + 2NOR01	
M.2	1 x M.2 M key Type 2242 (PCIe x 4), NVMe	
	1 x M.2 B key Type 3042 (PCIe x 1 / USB 2.0) ; WiFi / Bluetooth or PCIe	
	1 x M.2 B key Type 3042 (USB 3.1 / 2.0) ; 4G / 5G, GPS or USB Device	
I/O ports	Network	2 x Intel 2.5GbE I226IT ; 1 x GbE
	USB	4 x USB 3.1 (external) ;
		1 x USB 3.1 / 2.0 (Type C, OTG)
	Serial ports	2 x RS232 (Option RS422)
	CANBus	1 x CANBus (Option)
	Display	1 x HDMI®
	SIM Card	1 x Nano SIM
	DIO	4DI / 4DO (Option)
	Audio	Mic-in / Line-out
Internal I/O wafer	SPI, I²S, I²C, USB 2.0	
Optional Modules	M.2 Module: 4G, 5G, PCIe, WiFi, GPS, Bluetooth, NVMe	
& Accessory	DIN Rail Mounting Kit, VESA Mounting Kit, Wall Mounting Kit	

Mechanical

Dimensions	173W x 130D x 85H mm
Weight	2.6 kg
Mounting	DIN Rail Mount*, VESA Mount*, Wall Mount*


Power

DC input	Wide Range +9~36V
Ignition Option	ignition by module

Environment

Operating Temp. (100 % CPU usage)	-25°C to +60°C
Relative Humidity	95% @ 40°C, non-condensing

Dimension



Specification are subject to change without prior notice. ODM / OEM is available.