

Embedded Function Cards

CN034



DI/O Board

Features:

- 4 Digital Input + 4 Digital Output
- 8 x DI + 2 x DO (OEM)
- 72 x 35 mm

CN054



VGA Surge Protector

Features:

- VGA against lightning surge
- 30 x 31 mm

CN041



USB to 2 x Mini PCIe + 2 x SIM

Features:

- 2 x Mini PCI-e (Full size)
- 2 x SIM socket (Push-push)
- SIM card for GPRS / 3G / 3.5G
- 65 x 37 mm

CN055



SCSI Touch Panel

Features:

- CN055-SYS:
SCSI system LVDS connector board
- CN055-TM:
SCSI Touch Monitor connector board
- 20.5 x 110.1 mm

CN045



4 x RS232 at RJ45 connector

Features:

- 4 x RS232 2 x 5 pin 2.00mm Wafer
- Convert to 4 x RJ45 type connector
- 90.6 x 23 mm

CN058



Power on (Auto Boot) module



Features:

- Module input voltage: +9~36V (depends on MB)
- SBC turns on automatically when plugged in
- 30 x 30 mm

CN052



1 x SFP Fiber connector

Features:

- 1 x port 1000 Base-BX fiber
- Work with M213A
- 35x 45 mm

M422A+ Light Sensor



Light Sensor Control board

Features:

- USB to I2C interface + Light Sensor
- 31 x 30 mm

CN053



USB to 4 x Mini PCIe + 4 x SIM

Features:

- 4 x Mini PCI-e (Full size)
- 4 x Micro SIM socket (Push-push)
- 75 x 57 mm

Bluetooth Module



Bluetooth Module

Features:

- Bluetooth 2.0 + EDR support
- V1.1, V1.2, V2.0 compliant
- 30.61 x 15.02 mm