

# SKY 2-2I130DW

Fanless Embedded Computer with  
13th Gen Intel® Raptor Lake-U  
& 12th Intel® Alder Lake-U Processor



## Features:

- Intel® 13th Gen Raptor Lake-U, i7 / i5 / i3, Pentium CPU
- Intel® 12th Gen Alder Lake-U, i7 / i5 / i3, Celeron CPU
- 1 x DDR5 SODIMM (Max. 32GB)
- Multiple Independent display: 1 x HDMI®
- 4 x Intel 2.5 GbE LAN, 3 x USB 3.2, 2 x USB 2.0
- 1 x M.2 M Key, 1 x M.2 B Key, 1 x Nano SIM
- 2 x COM, 4DI / 4DO

## Specifications :

Motherboard	2I130DW	
CPU	13th Gen Raptor Lake-U, i7 / i5 / i3, Pentium CPU 12th Gen Alder Lake-U, i7 / i5 / i3, Celeron CPU	
Chipset	Intel Raptor Lake-U ; Alder Lake-U SoC	
Memory	1 x DDR5 SODIMM socket, Max. 32GB	
Storage	M.2-SSD, HDD / SSD	
Expansion slots	1 x M.2 M key Type 2280 (SATA / PCIe x 4), Support NVMe 1 x M.2 B key Type 2242 / 3042 (PCIe x2 / USB 3.2 / 2.0) 1 x Nano SIM	
I/O ports	Network	4 x Intel 2.5GbE
	USB	3 x USB 3.2 Gen 1 x 1, 2 x USB 2.0
	Serial ports	2 x RS232 / 422 / 485
	Display	1 x HDMI®
	GPIO	4 x DI / 4 x DO (Option)
Optional Modules & Accessory	*SATA Kit, *VESA Mounting Kit, DIN Rail Mounting Kit, *Wall Mount Kit *4G / 5G, WiFi, BT, Module, Digital I/O, 2 / 4 PoE	
OS Support	Windows® 10 IOT ; Windows® 11 IOT Ubuntu 22.04 above, Fedora 36 above	

## Mechanical

Dimensions	141W x 111.2D x 71.9H mm
Weight	1.25 kg
Mounting	VESA Mount* (VESA 75), DIN-Rail Mount*, Wall Mount*

## Power

DC input	9~36V
----------	-------

## Environment

Operating Temp. (100 % CPU usage)	-40°C ~ +60°C (under specific environmental & CPU power consumption conditions)
Relative Humidity	95% @ 40°C, non-condensing

## Certification

	CE / FCC class A
--	------------------

## Dimension

